AMENDMENTS TO THE CLAIMS

This Listing of Claims will replace all prior versions and listings of claims in this application.

Listing of Claims:

Claims 1 - 35. (Canceled)

- 36. (Currently amended) A container and lid combination comprising:
 - a) a container having a bottom and an upstanding wall having a rim at the open end said rim consisting of an internally rolled edge of the container wall;
 - b) a closure element adapted to seat on the rim, said element having an internal flange that abuts and sealingly engages the internal edge of the rim;
 - c) a lid <u>pivotally</u> attached to the closure element and having a dependent <u>peripheral</u> internal flange adapted to sealingly engage an internal edge of the closure element said lid being pivotable 180 degrees when fully opened and said peripheral flange ensuring that any liquid in the opened lid will be returned to the container when the lid is closed; and
 - d) a carry handle attached to the closure element and is pivotable between a carrying position and a stowed position.
- 37. (Currently amended) [[A]] The container and lid combination as claimed in claim 36 in which said dependent flange of the lid wipes past an internal sealing strip located on the flange of the closure element and extends past said sealing strip.
- 38. (Currently amended) [[A]] The container and lid combination as claimed in claim 37 in which said dependent flange of the lid is shaped to allow the lid to drain any contents back into the container.

39. (Currently amended) [[A]] The container and lid combination as claimed in claim 36 in

Docket No.: 21854-00050-US

which the closure element incorporates a pouring spout, adapted to guide the flow of the liquid

contents of the container, extending outwardly from the internal edge of the closure element

against which the lid sealingly engages.

40. (Currently amended) [[A]] The container and lid combination as claimed in claim 36 in

which the flange of the closure element incorporates a peripheral bead on its outer face to seat

below the container rim to retain the closure element on the container.

41. (Currently amended) [[A]] The container and lid combination as claimed in claim 36 in

which the lid hinges from the closed position to one or more open positions using a camming

surface associated with the hinge.

42. (Currently amended) [[A]] The container and lid combination as claimed in claim 36 in

which the upstanding wall incorporates an outwardly facing circumferential corrugation below

the rim.

43. (Currently amended) [[A]] The container and lid combination as claimed in claim 42

wherein the corrugation is spaced below the rim so that the closure element and lid can be

accommodated on the rim and the corrugation projects outwardly further than the peripheral

edge of the closure.

44. (Currently amended) [[A]] The container and lid combination as claimed in claim 36 in

which the handle is integrally moulded with the closure element.

45. (Currently amended) [[A]] The closure element for use in the container and lid combination

defined in claim 36 said closure element adapted to be mounted on an annular rim of a can and

consisting of comprising:

4

Application No. 10/518,709 Docket No.: 21854-00050-US

Amendment dated

Reply to Office Action of February 20, 2008

a) [[An]] an annular ring having a can rim sealing flange adapted to abut and sealingly engage with an internal edge of a can rim and an internal edge portion arranged to

define an opening;

b) a lid attached to the closure element and having a dependent internal flange adapted

to sealingly engage said internal edge of the closure element allowing sealing and re-

sealing of said opening with said lid; and

c) a carry handle attached to the closure element and is pivotable between a carrying

position and a stowed position.

46. (Currently amended) [[A]] The closure element as claimed in claim 45 in which the annular

ring has an annular wall spaced inwardly of said can rim sealing flange and the lid incorporates

a dependent flange which wipes past an internal sealing strip located on the inner wall of said

annular ring and extends past the sealing bead.

47. (Currently amended) [[A]] The closure element as claimed in claim 46 in which the

dependent peripheral flange of the lid is shaped to allow the lid to drain any contents back into

the container.

48. (Currently amended) [[A]] The closure element as claimed in claim 45 in which the ring

incorporates a pouring spout, adapted to guide the flow of the liquid contents of the container to

which the closure element is attached, extending outwardly from the inner wall of the ring

against which the lid sealingly abuts.

49. (Currently amended) [[A]] The closure element as claimed in claim 45 in which the lid

hinges from the closed position to one or more open positions using a camming surface

associated with the hinge.

5